Borel
Standard Furnaces & Ovens
Switzerland

CAR-HEARTH FURNACES 1200 °C
FM 1200

Definition: Chamber furnace with mobile hearth (trolley on rails).
Construction: Robust construction made of bent plate. Vertical lifting front door.
Insulation: Multilayer insulation. Interior in ceramic fibre and refractory bricks.
Aeration: Exhaust vent on top.
Heating: Coil resistors on ceramic tubes. The heating is turned off at the opening of the door.
Electricity: 3 x 400 VAC.
Regulation: Axron Swiss PID temperature controller.
Documentation: CE marking and operating instructions in English.
Delivered with: Removable ceramic sole.

Photos for illustration purposes only

MODEL	ITEM CODE	Int. Vol. (L)	Int. Dim. (WxHxD) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
FM 1200-27	N16347	27.4	280 x 280 x 350	590 x 790 x 700	4.5	84
FM 1200-45	N16348	45	300 x 300 x 500	660 x 770 x 720	6.0	106

Borel Swiss SA - A Division of SOLO Swiss Group
Place Pury, 3 - CH-2000 Neuchâtel - Switzerland

Tel : +41 (0)32 756 64 00
Fax : +41 (0)32 756 64 48

mail@borel.eu
www.borel.eu