

Borel

Standard Furnaces & Ovens

Switzerland



Photos for illustration purposes only

CHAMBER FURNACES 1200 °C FP 1200

Definition: Electric chamber furnace for all applications.

Construction: Robust construction made of bent plate. Vertical lifting front door.

Insulation: Multilayer insulation. Interior in ceramic fibre and refractory bricks.

Aeration: Rear exhaust.

Heating: Coil resistors on ceramic tubes. The heating is turned off at the opening of the door.

Electricity: 18 liters and less, single-phase 230 VAC, 50 Hz. From 25 liters, 3 x 400 VAC.

Regulation: Axron Swiss PID temperature controller.

Documentation: CE marking and operating instructions in English.

Delivered with:

Removable ceramic sole.



MODEL	ITEM CODE	Int. Vol. (L)	Int. Dim. (WxHxD) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
FP 1200-5	G14979	5	180 x 140 x 200	550 x 650 x 580	2.4	56
FP 1200-7	G14980	7.3	200 x 140 x 250	550 x 650 x 580	2.4	59
FP 1200-10	G14981	10	200 x 200 x 250	560 x 720 x 670	4.0	62
FP 1200-12	G14970	12	200 x 200 x 300	560 x 720 x 670	4.0	65
FP 1200-15	G14982	15	220 x 230 x 300	560 x 720 x 670	4.0	69
FP 1200-18	G14983	18	230 x 230 x 350	590 x 790 x 700	4.0	73
FP 1200-27	G14984	27.4	280 x 280 x 350	590 x 790 x 700	5.0	84
FP 1200-45	G14985	45	300 x 300 x 500	660 x 770 x 720	6.9	106
FP 1200-60	G14994	60	400 x 300 x 500	760 x 810 x 840	6.9	140

SOLO Swiss SA

Grandes-Vies, 25 - CH-2900 Porrentruy - Switzerland

Tel : +41 (0)32 756 64 00

Fax : +41 (0)32 465 96 05

borel@soloswiss.com

www.borel.eu