

Borel

Standard Furnaces & Ovens

Switzerland



Photos for illustration purposes only

OPENING TUBE FURNACES 1100 °C TO 1100

Definition: Opening electric tube furnace for all applications.

Construction: Robust construction made of bent plate.

Insulation: Multilayer insulation. Interior in ceramic fibre and refractory bricks.

Heating: Working chamber surrounded by heating elements.

Electricity: Voltage 230 VAC, 50 Hz up to 4 kW and voltage 3x400 VAC frequency 50 Hz from 4 kW.

Regulation: Axron Swiss PID temperature controller.

Documentation: CE marking and operating instructions in English.



MODEL	ITEM CODE	Heated Length (mm)	Tube Dim. (Øxlength) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)
TO 1100-70-250	N16386	250	70	400 x 510 x 500	2.0
TO 1100-70-500	N16387	500	70	650 x 510 x 500	2.4
TO 1100-100-250	N16388	250	100	400 x 510 x 500	2.4
TO 1100-100-500	N16389	500	100	650 x 510 x 500	3.0
TO 1100-150-250	N16390	250	130	400 x 560 x 570	3.0
TO 1100-150-500	N16391	500	130	650 x 560 x 570	3.5
TO 1100-200-250	N16392	250	160	400 x 560 x 570	3.0
TO 1100-200-500	N16393	500	160	650 x 560 x 570	3.5
TO 1100 250-375	N16394	375	200	555 x 710 x 740	6.0
TO 1100-300-400	N16395	400	250	555 x 810 x 860	9.0

SOLO Swiss SA

Grandes-Vies, 25 - CH-2900 Porrentruy - Switzerland

Tel : +41 (0)32 756 64 00

Fax : +41 (0)32 465 96 05

borel@soloswiss.com

www.borel.eu